



LEFKADA

Name:	Lefkada
Built:	2016
Flag:	Liberia
Class:	NKK
Type:	Craned double-hull single-deck bulk carrier, boxshaped
Dwat:	37,951 mts on 10.54 m ssw 36,888 mts on 10.32 m wsw
Tpc:	48.60 mts on summer draft
L.o.a.:	179.97 m
Beam:	29.80 m
Moulded depth:	15.00 m



Distance water line to top of hatch coaming in normal ballasted condition:					
forward hatch: 11.30 m midships: 10.88 m aft hatch: 10.45 m					
Tonnage:	(International):	gt/nt	23,306 / 12,101		
Hatches:	5				
Hatch sizes:	No. 1	15.86 m x 17.16 m			
	No. 2	20.04 m x 20.02 m			
	No. 3	20.04 m x 20.02 m			
	No. 4	20.04 m x 20.02 m			
	No. 5	20.04 m x 20.02 m			
Type of hatchcovers:	Foldable hydraulic hatch covers				
Hold:	Sizes:	Length	Breadth (fore/aft)	Height	Grain / Bale (cub.m)
	No 1:	27.55 m	7.80 m / 22.80 m	13.60 m	7,707.42 / 7,380.05
	No 2:	27.55 m	25.80 m	13.60 m	9,932.75 / 9,575.67
	No 3:	27.55 m	25.80 m	13.60 m	9,966.82 / 9,578.52
	No 4:	27.55 m	25.80 m	13.60 m	9,955.17 / 9,577.34
	No 5:	27.55 m	25.80 m / 9.60 m	13.60 m	9,432.71 / 9,126.15
Total capacity in cubic meters:					46,994.86 / 45,238.33
Gear:	4 cranes x 30.5 mts				
Tanktop strength:	No. 1: 20.68 mts/sqm, No. 2/4: 15.05 mts/sqm, No. 3: 20.00 mts/sqm, No. 5: 20.08 mts/sqm				
Ventilation:	Natural				
Speed/consumption:	About 14.0 kn on about 24.0 mts IFO 380 cst, all incl. A/E, nil MDO at sea About 12.5 kn on about 17.5 mts IFO 380 cst, all incl. A/E, nil MDO at sea				
Port consumption:	Idle about 2.3 mts IFO 380 cst				
Winches working:	About 3.0 mts IFO 380 cst (Note: Local port regulations require the burning of MGO in port, e.g. EU ports)				

All about, taken from plan but without guarantee.

SEA STALLION POOL INC.

Commercial Manager: Aug. Bolten Wm. Miller's Nachfolger (GmbH & Co.) KG · Mattentwiete 8 · 20457 Hamburg · Germany
Phone +49 (0)40/3601-366 · Fax +49 (0)40/3601-364 · E-Mail chartering@aug-bolten.de